

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

**SECTION 1. IDENTIFICATION**

Product name : MOLYKOTE(R) 316 SILICONE RELEASE SPRAY

Product code : 000000000001895371

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Anti-set off and adhesive agents

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Flammable aerosols : Category 1

Gases under pressure : Dissolved gas

Skin irritation : Category 2

Specific target organ systemic toxicity - single exposure : Category 3

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.

MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
Chemical nature : Hydrocarbon aerosol propellant

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha, Petroleum, Light Alkylate	64741-66-8	>= 47 - <= 55
Propane	74-98-6	>= 20 - <= 25
Butane	106-97-8	>= 15 - <= 18

**SECTION 4. FIRST AID MEASURES**

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.

# MOLYKOTE(R) 316 SILICONE RELEASE SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

- |   |  |
|---|--|
| In case of skin contact                                     | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse. |
| In case of eye contact                                      | : Flush eyes with water as a precaution.<br>Get medical attention if irritation develops and persists.   |
| If swallowed  | : If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water.  |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.<br>May cause drowsiness or dizziness.  |
| Protection of first-aiders                                  | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.  |
| Notes to physician  | : Treat symptomatically and supportively.  |

## SECTION 5. FIRE-FIGHTING MEASURES

- |  |   |
|--|---|
| Suitable extinguishing media                   | : Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical  |
| Unsuitable extinguishing media                 | : None known.   |
| Specific hazards during fire fighting          | : Flash back possible over considerable distance.<br>Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health.<br>If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products                  | : Carbon oxides<br>Silicon oxides<br>Formaldehyde   |
| Specific extinguishing methods                 | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers.<br>Remove undamaged containers from fire area if it is safe to do so.<br>Evacuate area.                   |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.<br>Use personal protective equipment.  |

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use with local exhaust ventilation.  
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
- Advice on safe handling : Do not spray on an open flame or other ignition source.  
  
Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY

Version 5.0      Revision Date: 11/13/2017      SDS Number: 1147811-00007      Date of last issue: 03/21/2017  
Date of first issue: 02/03/2015

- Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha, Petroleum, Light Alkylate	64741-66-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
Butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		STEL	1,000 ppm	ACGIH

- Engineering measures : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential  
Use with local exhaust ventilation.

## Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a dissolved gas

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version 5.0	Revision Date: 11/13/2017	SDS Number: 1147811-00007	Date of last issue: 03/21/2017 Date of first issue: 02/03/2015
----------------	------------------------------	------------------------------	---

Color	:	colorless
Odor	:	solvent
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	-91 °C Method: Tag closed cup
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.1
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

Particle size : Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
Use at elevated temperatures may form highly hazardous compounds.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

Thermal decomposition : Formaldehyde

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute dermal toxicity : Acute toxicity estimate: 4,892 mg/kg  
Method: Calculation method

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity



MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

Acute dermal toxicity : LD50 (Rabbit): > 2,200 - 2,500 mg/kg  
Remarks: Based on data from similar materials

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Skin corrosion/irritation**

Causes skin irritation.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Test Type: Buehler Test  
Routes of exposure: Skin contact  
Species: Guinea pig  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Genotoxicity in vitro	: Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Inhalation Result: negative

**Propane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative

**Butane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Species: Mouse
Application Route: Skin contact
Exposure time: 102 weeks
Result: negative

**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Inhalation Result: negative
----------------------	---	--

**Propane:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
------------------------------	---	--

**Butane:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
------------------------------	---	--

**STOT-single exposure**

May cause drowsiness or dizziness.

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Assessment: May cause drowsiness or dizziness.

**Propane:**

Assessment: May cause drowsiness or dizziness.

**Butane:**

Assessment: May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Species: Rat  
NOAEL: 10 mg/l  
Application Route: inhalation (vapor)  
Exposure time: 13 Weeks  
Method: OPPTS 870.3465

**Propane:**

Species: Rat  
NOAEL: 7.214 mg/l  
Application Route: inhalation (gas)  
Exposure time: 6 Weeks  
Method: OECD Test Guideline 422

**Butane:**

Species: Rat  
NOAEL: 9000 ppm  
Application Route: inhalation (gas)  
Exposure time: 6 Weeks  
Method: OECD Test Guideline 422

**Aspiration toxicity**

Not classified based on available information.

**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

**Persistence and degradability****Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 77 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---	---

**Propane:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	---	--

**Butane:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	---	--

**Bioaccumulative potential****Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Partition coefficient: n-	:	log Pow: > 4
---------------------------	---	--------------

MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

|| octanol/water

Remarks: Based on data from similar materials

**Butane:**|| Partition coefficient: n-  
|| octanol/water

: log Pow: 2.31

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

Waste Code : D001: Ignitability

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950

Proper shipping name : AEROSOLS

|| Class : 2.1

Packing group : Not assigned by regulation

|| Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

|| Class : 2.1

Packing group : Not assigned by regulation

|| Labels : Flammable Gas

|| Packing instruction (cargo) : 203

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

aircraft)  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
(Naphtha, Petroleum, Light Alkylate)

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 1950  
Proper shipping name : Aerosols

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : FLAMMABLE GAS  
ERG Code : 126  
Marine pollutant : yes(Naphtha, Petroleum, Light Alkylate)

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Skin corrosion or irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**US State Regulations****Pennsylvania Right To Know**

Naphtha, Petroleum, Light Alkylate

64741-66-8

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

Propane	74-98-6
Butane	106-97-8
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**California List of Hazardous Substances**

Butane	106-97-8
--------	----------

**California Permissible Exposure Limits for Chemical Contaminants**

Propane	74-98-6
Butane	106-97-8

**The ingredients of this product are reported in the following inventories:**

NZIoC	: All ingredients listed or exempt.
TSCA	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
KECI	: All ingredients listed, exempt or notified.
PICCS	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	: All ingredients listed or exempt.




MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

## SECTION 16. OTHER INFORMATION

## Further information

## NFPA:



## HMIS® IV:

HEALTH	/	2
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 NIOSH REL : USA. NIOSH Recommended Exposure Limits  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
 ACGIH / STEL : Short-term exposure limit  
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
 OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of

**MOLYKOTE(R) 316 SILICONE RELEASE  
SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/21/2017
5.0	11/13/2017	1147811-00007	Date of first issue: 02/03/2015

---

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/13/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8