



SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® L-0501 High Performance
Penetrating Lubricant

Issue Date: 03/19/2019

Print Date: 01/28/2021

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MOLYKOTE® L-0501 High Performance Penetrating Lubricant

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION

DDP SPECIALTY ELECTRONIC MATERIALS
US 9, LLC
974 Centre Road
Wilmington DE 19805
UNITED STATES

Customer Information Number:

833-338-7668
SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage - Category 1

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Causes serious eye damage.

Precautionary statements

Prevention

Avoid breathing spray.

Use only outdoors or in a well-ventilated area.

Wear eye protection/ face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Organic compounds., in mineral oil

This product is a mixture.

Component	CASRN	Concentration
Distillates (petroleum), hydrotreated light	64742-47-8	>= 50.0 - < 60.0 %
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 40.0 - < 50.0 %
Zinc di(2-ethylhexyl) dithiophosphate	4259-15-8	>= 5.0 - < 10.0 %
Naphthalenesulfonic acid, dinonyl-, calcium salt	57855-77-3	>= 1.0 - < 5.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Metal oxides Oxides of phosphorus Nitrogen oxides (NO_x) Sulphur oxides

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Distillates (petroleum), hydrotreated light	OSHA Z-1	TWA	2,000 mg/m ³ 500 ppm
	ACGIH	TWA	200 mg/m ³ , total hydrocarbon vapor
	OSHA Z-1	TWA Mist	5 mg/m ³
	CAL PEL	PEL particulate	5 mg/m ³
Distillates (petroleum), hydrotreated heavy naphthenic	OSHA Z-1	TWA Mist	5 mg/m ³
	ACGIH	TWA Inhalable fraction	5 mg/m ³
	CAL PEL	PEL particulate	5 mg/m ³

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	amber
Odor	slight
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 65 °C (> 149 °F)
Flash point	Pensky-Martens closed cup 101.67 °C (215.01 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available

Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.86
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	32.1 mPa.s
Kinematic Viscosity	No data available
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. Excessive exposure may cause irritation to upper respiratory tract (nose and throat).

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Repeated contact may cause severe skin irritation with local redness and discomfort.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data for the component(s), repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

No relevant data found.

Teratogenicity

Contains component(s) which, in laboratory animals, have been toxic to the fetus only at doses toxic to the mother.

Reproductive toxicity

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

COMPONENTS INFLUENCING TOXICOLOGY:

Distillates (petroleum), hydrotreated light

Acute inhalation toxicity

Prolonged exposure is not expected to cause adverse effects.

Based on data from similar materials LC50, Rat, 4 Hour, dust/mist, > 5.3 mg/l

Distillates (petroleum), hydrotreated heavy naphthenic

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 5.53 mg/l OECD Test Guideline 403

Zinc di(2-ethylhexyl) dithiophosphate

Acute inhalation toxicity

The LC50 has not been determined.

Naphthalenesulfonic acid, dinonyl-, calcium salt

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Prolonged excessive exposure may cause adverse effects.

LC50, Rat, 1 Hour, dust/mist, > 9,000 mg/l

Carcinogenicity

Component

Distillates (petroleum),
hydrotreated light

List

ACGIH

Classification

A3: Confirmed animal carcinogen with
unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Distillates (petroleum), hydrotreated light

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis
(LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LL50, Danio rerio (zebra fish), 96 Hour, > 250 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EL50, Acartia tonsa, 48 Hour, > 3,193 mg/l

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, > 3,200 mg/l
NOELR, Skeletonema costatum (marine diatom), 72 Hour, 993 mg/l

Chronic toxicity to aquatic invertebrates

NOELR, Ceriodaphnia dubia (water flea), 8 d, > 70 mg/l

Distillates (petroleum), hydrotreated heavy naphthenic

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LL50, Pimephales promelas (fathead minnow), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EL50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

NOELR, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

NOEC, 10 min, >= 1.93 mg/l

Chronic toxicity to aquatic invertebrates

NOELR, Daphnia magna (Water flea), 21 d, 10 mg/l

Zinc di(2-ethylhexyl) dithiophosphate

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LL50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.4 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EL50, Daphnia magna (Water flea), Static, 48 Hour, 75 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EL50, Scenedesmus subspicatus, Static, 72 Hour, Growth rate, 410 mg/l, OECD Test Guideline 201

NOELR, Scenedesmus subspicatus, Static, 72 Hour, 220 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, Pseudomonas putida, 16 Hour, 380 mg/l

Chronic toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 0.4 mg/l

Naphthalenesulfonic acid, dinonyl-, calcium salt

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

For similar material(s):

No toxicity at the limit of solubility

LC50, Cyprinus carpio (Carp), 96 Hour, > 0.28 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For similar material(s):

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), 48 Hour, > 0.18 mg/l, OECD Test Guideline 202

Toxicity to bacteria

For similar material(s):

EC50, 3 Hour, 560 mg/l, OECD Test Guideline 209

Persistence and degradability

Distillates (petroleum), hydrotreated light

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 82 %

Exposure time: 24 d

Method: OECD Test Guideline 301F

Distillates (petroleum), hydrotreated heavy naphthenic

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

Biodegradation: 31 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Zinc di(2-ethylhexyl) dithiophosphate

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: < 5 %

Exposure time: 27 d

Method: Directive 67/548/EEC, Annex V, C.6

Naphthalenesulfonic acid, dinonyl-, calcium salt

Biodegradability: For similar material(s):

10-day Window: Fail

Biodegradation: 17 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

Distillates (petroleum), hydrotreated light

Bioaccumulation: No relevant data found.

Distillates (petroleum), hydrotreated heavy naphthenic

Bioaccumulation: No relevant data found.

Zinc di(2-ethylhexyl) dithiophosphate

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.59 OECD Test Guideline 107

Bioconcentration factor (BCF): < 100 Cyprinus carpio (Carp)

Naphthalenesulfonic acid, dinonyl-, calcium salt

Bioaccumulation: No relevant data found.

Mobility in soil

Distillates (petroleum), hydrotreated light

No relevant data found.

Distillates (petroleum), hydrotreated heavy naphthenic

No relevant data found.

Zinc di(2-ethylhexyl) dithiophosphate

No specific, relevant data available for assessment.

Naphthalenesulfonic acid, dinonyl-, calcium salt

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components

CASRN

Zinc di(2-ethylhexyl) dithiophosphate

4259-15-8

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components

CASRN

Distillates (petroleum), hydrotreated light

64742-47-8

Distillates (petroleum), hydrotreated heavy naphthenic

64742-52-5

Zinc di(2-ethylhexyl) dithiophosphate

4259-15-8

Undisclosed components

Not Assigned

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
3	1	0

HMIS

Health	Flammability	Physical Hazard
3/	1	0

Revision

Identification Number: 4052332 / A776 / Issue Date: 03/19/2019 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	Permissible exposure limit
TWA	8-hour time weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for

Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US