

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version Revision Date: SDS Number: Date of last issue: 06/21/2017
4.0 09/07/2017 649889-00010 Date of first issue: 10/20/2014

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Product code : 000000000004033112

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Inorganic and organic compounds
Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	>= 53 - <= 63
Calcium carbonate	471-34-1	>= 2.8 - <= 3.2
Aluminum hydroxide benzoate stearate	54326-11-3	>= 2.4 - <= 2.8
Zinc oxide	1314-13-2	>= 1.8 - <= 2

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
4.0	09/07/2017	649889-00010	Date of first issue: 10/20/2014

- | | | |
|---|---|---|
| In case of skin contact | : | Wash with water and soap as a precaution.
Get medical attention if symptoms occur. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | None known. |
| Protection of first-aiders | : | No special precautions are necessary for first aid responders. |
| Notes to physician | : | Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire fighting | : | Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides
Metal oxides
Oxides of phosphorus
Sulfur oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Follow safe handling advice and personal protective equipment recommendations. |
|---|---|--|

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
 Date of first issue: 10/20/2014

- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version
4.0Revision Date:
09/07/2017SDS Number:
649889-00010Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Aluminum hydroxide benzoate stearate	54326-11-3	TWA	10 mg/m ³	ACGIH
Zinc oxide	1314-13-2	TWA (Respirable fraction)	2 mg/m ³	ACGIH
		STEL (Respirable fraction)	10 mg/m ³	ACGIH
		TWA (Dust)	5 mg/m ³	NIOSH REL
		TWA (Fumes)	5 mg/m ³	NIOSH REL
		ST (Fumes)	10 mg/m ³	NIOSH REL
		C (Dust)	15 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Fumes)	5 mg/m ³	OSHA Z-1

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium carbonate

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : white

Odor : slight

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : > 200 °C
Method: closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

Relative vapor density : No data available

Relative density : 1.15

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.
When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. Safe handling conditions may be maintained by keeping vapor concentrations within the occupational exposure limit for formaldehyde.
See OSHA formaldehyde standard, 29 CFR 1910.1048
Formaldehyde may cause cancer. It is also toxic by inhalation, skin absorption and ingestion, corrosive to skin and eyes, and may cause skin sensitization and respiratory irritation.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Aluminum hydroxide benzoate stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

||

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Species: Rabbit
Result: No skin irritation

Calcium carbonate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Aluminum hydroxide benzoate stearate:

Method: OECD Test Guideline 439
Result: No skin irritation

Zinc oxide:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Species: Rabbit
Result: No eye irritation

Calcium carbonate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

Aluminum hydroxide benzoate stearate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Zinc oxide:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Calcium carbonate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Aluminum hydroxide benzoate stearate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Zinc oxide:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Germ cell mutagenicity

Not classified based on available information.

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
 Date of first issue: 10/20/2014

Ingredients:**White mineral oil (petroleum):**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Calcium carbonate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
 Result: negative

Aluminum hydroxide benzoate stearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Result: negative

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Rat
 Application Route: Inhalation
 Method: OECD Test Guideline 474
 Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Species: Rat
 Application Route: Ingestion
 Exposure time: 24 Months
 Result: negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Aluminum hydroxide benzoate stearate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Hamster
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Zinc oxide:**

Routes of exposure: inhalation (dust/mist/fume)
Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity**Ingredients:****White mineral oil (petroleum):**

Species: Rat
LOAEL: 160 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Species: Rat
LOAEL: >= 1 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Method: OECD Test Guideline 412

Calcium carbonate:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Aluminum hydroxide benzoate stearate:

Species: Rat
NOAEL: > 225 mg/kg
Application Route: Ingestion

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
 Date of first issue: 10/20/2014

Exposure time: 54 Days
 Method: OECD Test Guideline 422
 Remarks: Based on data from similar materials

Zinc oxide:

Species: Rat
 NOAEL: 1.5 mg/m³
 Application Route: inhalation (dust/mist/fume)
 Exposure time: 3 Months
 Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****White mineral oil (petroleum):**

<p>Toxicity to fish</p> <p>Toxicity to daphnia and other aquatic invertebrates</p> <p>Toxicity to algae</p> <p>Toxicity to fish (Chronic toxicity)</p> <p>Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)</p>	<p>: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203</p> <p>: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202</p> <p>: NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201</p> <p>: NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l Exposure time: 28 d</p> <p>: NOEC (Daphnia magna (Water flea)): 1,000 mg/l Exposure time: 21 d</p>
--	---

Calcium carbonate:

<p>Toxicity to fish</p> <p>Toxicity to daphnia and other aquatic invertebrates</p> <p>Toxicity to algae</p>	<p>: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203</p> <p>: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202</p> <p>: ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Method: OECD Test Guideline 201</p>
---	---

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
 Date of first issue: 10/20/2014

II

Aluminum hydroxide benzoate stearate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Zinc oxide:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 330 - 780 µg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 6.9 - 16.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Selenastrum capricornutum (green algae)): 136 µg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Selenastrum capricornutum (green algae)): 24 µg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: 1
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 199 µg/l Exposure time: 30 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 37 µg/l Exposure time: 21 d Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	: 1
Toxicity to microorganisms	: EC50: 5.2 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

Persistence and degradability**Ingredients:****White mineral oil (petroleum):**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Aluminum hydroxide benzoate stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Ingredients:****Zinc oxide:**

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 177

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
4.0	09/07/2017	649889-00010	Date of first issue: 10/20/2014

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc sulfide	1314-98-3	>= 8 - <= 10 %
Zinc oxide	1314-13-2	>= 1.8 - <= 2 %

US State Regulations**Pennsylvania Right To Know**

White mineral oil (petroleum)	8042-47-5
Tricalcium Phosphate, Hydrated	1306-06-5
Zinc sulfide	1314-98-3
Calcium carbonate	471-34-1
Zinc oxide	1314-13-2

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

White mineral oil (petroleum)	8042-47-5
Zinc sulfide	1314-98-3
Zinc oxide	1314-13-2

California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum)	8042-47-5
Calcium carbonate	471-34-1
Zinc oxide	1314-13-2

The ingredients of this product are reported in the following inventories:

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE


Version 4.0 Revision Date: 09/07/2017 SDS Number: 649889-00010 Date of last issue: 06/21/2017
Date of first issue: 10/20/2014

- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : All ingredients listed or exempt.
- IECSC : All ingredients listed or exempt.
- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- PICCS : Consult your local Dow Corning office.
- TCSI : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
4.0	09/07/2017	649889-00010	Date of first issue: 10/20/2014

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/07/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) P-1900 FM ANTI-SEIZE PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
4.0	09/07/2017	649889-00010	Date of first issue: 10/20/2014

relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8