MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE® L-0660 Ammonia Refrigerant Compressor Oil

Product code : 04041789

Manufacturer or supplier's details

Company Identification : DDP SPECIALTY ELECTRONIC MATERIALS

US 9, LLC 974 Centre Road Wilmington DE 19805 UNITED STATES

Telephone : 833-338-7668

24-Hour Emergency Contact : 1-800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion-NA@dupont.com

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Inorganic and organic compounds

in mineral oil

Hazardous ingredients

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| White mineral oil (petroleum) | 8042-47-5 | >= 90 - <= 100 |
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides

Specific extinguishing meth-

ods.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

Follow safe handling advice and personal protective

equipment recommendations.

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

gency procedures

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| • | • | | | |
|-------------------------------|-----------|----------------|--------------------|----------|
| Ingredients | CAS-No. | Value type | Control parame- | Basis |
| | | (Form of | ters / Permissible | |
| | | exposure) | concentration | |
| White mineral oil (petroleum) | 8042-47-5 | TWA (Mist) | 5 mg/m³ | OSHA Z-1 |
| | | TWA (Inhal- | 5 mg/m³ | ACGIH |
| | | able fraction) | | |

MOLYKOTE® L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

| II | | TWA (Mist) | 5 mg/m³ | NIOSH REL |
|--|------------|------------|----------------------|-----------|
| | | ST (Mist) | 10 mg/m ³ | NIOSH REL |
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | TWA (Mist) | 5 mg/m³ | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m³ | NIOSH REL |
| | | ST (Mist) | 10 mg/m ³ | NIOSH REL |

Engineering measures Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection Wear the following personal protective equipment:

Safety glasses

Skin should be washed after contact. Skin and body protection

Hygiene measures Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Chemical customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

Color : Colorless to pale yellow

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

> 35 °C

Flash point : 226 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.87

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 70 mm²/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Species: Rabbit

Result: No skin irritation

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Species: Rabbit

Result: No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

II

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Species: Rat

Application Route: Ingestion Exposure time: 24 Months

Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Skin contact

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

White mineral oil (petroleum):

Species: Rat

LOAEL: > 160 mg/kg Application Route: Ingestion Exposure time: 90 Days

Species: Rat LOAEL: >= 1 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Method: OECD Test Guideline 412

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version 3.0

Revision Date: 10/22/2018

SDS Number: 1242820-00008

Date of last issue: 05/02/2017 Date of first issue: 02/05/2015

П

Aspiration toxicity

Not classified based on available information.

Ingredients:

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 28 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 21 d

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Persistence and degradability

Ingredients:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version 3.0

Revision Date: 10/22/2018

SDS Number: 1242820-00008

Date of last issue: 05/02/2017 Date of first issue: 02/05/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA)

: This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

| Ingredients | CAS-No. | Component RQ | Calculated product RQ |
|----------------|----------|--------------|-----------------------|
| | | (lbs) | (lbs) |
| Ethyl acrylate | 140-88-5 | 1000 | * |

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

White mineral oil (petroleum) 8042-47-5
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7
Oxidation and antifoam additives Not Assigned

California Prop. 65

WARNING: This product can expose you to chemicals including Ethyl acrylate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

White mineral oil (petroleum) 8042-47-5 Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7

California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum) 8042-47-5 Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7

The ingredients of this product are reported in the following inventories:

REACH : All ingredients (pre-)registered or exempt.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

MOLYKOTE[®] L-0660 Ammonia Refrigerant Compressor Oil




Version Revision Date: SDS Number: Date of last issue: 05/02/2017 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DOT - Department of Transportation: DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)

MOLYKOTE® L-0660 Ammonia Refrigerant Compressor Oil



Version SDS Number: Date of last issue: 05/02/2017 Revision Date: 3.0 10/22/2018 1242820-00008 Date of first issue: 02/05/2015

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 10/22/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8