according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Capstone™ FS-3100

Product code : D14561064

SDS-Identcode : 130000095223

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only.

Do not use or resell Chemours[™] materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information,

please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Specific target organ toxicity : Category 2 (spleen)

repeated exposure

Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).

GHS label elements

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Hazard pictograms





Signal Word : Warning

Hazard Statements : H302 Harmful if swallowed.

H373 May cause damage to organs (spleen) through prolonged

or repeated exposure.

Precautionary Statements : Prevention:

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel

unwell. Rinse mouth.

P314 Get medical attention if you feel unwell.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-

tridecafluorooctyl) ether

CAS-No. : 52550-44-4

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8 ,8-tridecafluorooctyl) ether	52550-44-4*	>= 80 - <= 100	TSC

^{*} Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Lung edema

Shortness of breath

Eye contact may provoke the following symptoms

Irritation Lachrymation Redness Discomfort

Ingestion may provoke the following symptoms:

Nausea Vomiting Diarrhea tearing Redness Discomfort

Harmful if swallowed.

May cause damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire : Exposure to combustion products may be a hazard to health.

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

fighting

Hazardous combustion prod: :

ucts

Hydrogen fluoride carbonyl fluoride

potentially toxic fluorinated compounds

aerosolized particulates

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe mist or vapors.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		С	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/04/2024

 12.0
 07/22/2025
 1338340-00051
 Date of first issue: 02/27/2017

		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m³	NIOSH REL
		С	200 ppm 229 mg/m³	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : G

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks

and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : yellow, amber

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Solubility(ies)

Water solubility : slightly soluble

Partition coefficient: n-

octanol/water

No data available

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Autoignition temperature : No data available

Decomposition temperature : > 392 °F / > 200 °C

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride

Carbonyl difluoride Carbon dioxide Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 415.38 mg/kg

Method: Calculation method

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Acute oral toxicity : LD50 (Rat): 410 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Germ cell mutagenicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (spleen) through prolonged or repeated exposure.

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Target Organs : spleen

Assessment : Shown to produce significant health effects in animals at con-

centrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Species: MouseNOAEL: 30 mg/kgLOAEL: 125 mg/kgApplication Route: IngestionExposure time: 28 d

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 36.7 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 28.8 mg/l

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88.3

plants mg/l Exposure time: 72 h

EbC50 (Pseudokirchneriella subcapitata (green algae)): 50.3

mg/l

Exposure time: 72 h

EyC50 (Pseudokirchneriella subcapitata (green algae)): 50.1

mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Components:

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) ether:

Results of PBT and vPvB : Substance is not persistent, bioaccumulative, and toxic (PBT).

assessment

Endocrine disrupting poten: Substance does not have endocrine disrupting properties.

tial

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
1,4-Dioxane	123-91-1	100	105263

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8- 52550-44-4

tridecafluorooctyl) ether

1,4-Dioxane 123-91-1

California Prop. 65

WARNING: This product can expose you to chemicals including 1,4-Dioxane, which is/are known to the State of California to cause cancer, and

Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional regulatory information

Polyethylene oxide, mono(3,3,4,4,5,5,6,6,7,7,8,8,8tridecafluorooctyl) ether 52550-44-4

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/04/2024

 12.0
 07/22/2025
 1338340-00051
 Date of first issue: 02/27/2017

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.10515

This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR).


This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

P-10-0060

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

Version Revision Date: SDS Number: Date of last issue: 11/04/2024 12.0 07/22/2025 1338340-00051 Date of first issue: 02/27/2017

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 07/22/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

according to the OSHA Hazard Communication Standard



Capstone™ FS-3100

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/04/2024

 12.0
 07/22/2025
 1338340-00051
 Date of first issue: 02/27/2017

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8