

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Product code : 000000000001512854

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use


Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Other hazards

None known.

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
 Date of first issue: 11/25/2014

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Molybdenum disulfide grease

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 38 - <= 46
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 34 - <= 41
12-Hydroxy lithium stearate	7620-77-1	>= 7 - <= 8
Residual oils (petroleum), solvent-dewaxed	64742-62-7	>= 3 - <= 5
Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts	68457-79-4	>= 3 - <= 4
Graphite	7782-42-5	>= 0.9 - <= 1.3

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye damage.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
 - Unsuitable extinguishing media : None known.
 - Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
 - Hazardous combustion products : Carbon oxides
Metal oxides
Oxides of phosphorus
Sulfur oxides
 - Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
 - Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m ³	ACGIH
Residual oils (petroleum), solvent-dewaxed	64742-62-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
 Date of first issue: 11/25/2014

		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts	68457-79-4

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

- resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Grease
- Color : black
- Odor : slight
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : > 200 °C
Method: closed cup
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
- Upper explosion limit / Upper flammability limit : No data available

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 0.89

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Residual oils (petroleum), solvent-dewaxed:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 hrs
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

- Acute oral toxicity : LD50 (Rat): 3,600 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Graphite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit
Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Species: Rabbit
Result: Skin irritation

Graphite:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Species: Rabbit
Result: Irreversible effects on the eye

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

Graphite:

Species: Rabbit
Result: No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Residual oils (petroleum), solvent-dewaxed:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Graphite:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

: Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

: Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Residual oils (petroleum), solvent-dewaxed:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative
Remarks: Based on data from similar materials

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**12-Hydroxy lithium stearate:**

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat

NOAEL: > 0.98 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 Weeks
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rat
NOAEL: > 88 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Residual oils (petroleum), solvent-dewaxed:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Method: OECD Test Guideline 411
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Species: Rat
NOAEL: 160 mg/kg
Application Route: Ingestion
Exposure time: 28 - 40 Days
Method: OECD Test Guideline 422

Graphite:

Species: Rat
NOAEL: 12 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days
Method: OECD Test Guideline 412

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Aspiration toxicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), hydrotreated heavy naphthenic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Toxicity to microorganisms : NOEC: >= 1.93 mg/l
Exposure time: 10 min

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Residual oils (petroleum), solvent-dewaxed:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: Water Accommodated Fraction
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): 4.5 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 23 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): 24 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.4 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

**MOLYKOTE(R) BR-2 PLUS HIGH
PERFORMANCE GREASE**

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Residual oils (petroleum), solvent-dewaxed:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential**Ingredients:**

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts:

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014

Partition coefficient: n-octanol/water : log Pow: 0.69

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
 Date of first issue: 11/25/2014

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts	68457-79-4	>= 3 - <= 4 %
Zinc sulfide	1314-98-3	>= 0.58 - <= 0.97 %
Zinc oxide	1314-13-2	0.0016 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
12-Hydroxy lithium stearate	7620-77-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts	68457-79-4
Graphite	7782-42-5

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Phosphorodithioic Acid, mixed O,O-bis(iso-Bu andPentyl) Esters, Zinc Salts	68457-79-4
Graphite	7782-42-5

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Graphite	7782-42-5

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 5.2 Revision Date: 03/18/2017 SDS Number: 826025-00009 Date of last issue: 09/28/2016
Date of first issue: 11/25/2014


representative/local office.

- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- PICCS : All ingredients listed or exempt.
- KECI : All ingredients listed, exempt or notified.
- IECSC : All ingredients listed or exempt.
- AICS : All ingredients listed or exempt.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- TCSI : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	/	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/18/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 09/28/2016
5.2	03/18/2017	826025-00009	Date of first issue: 11/25/2014

shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8